

**AMENDMENTS TO THE CLAIMS**

1. (Canceled)
2. (Currently amended) An [[The]] oscillator device according to claim 1, comprising: an oscillation circuit substrate; an oscillation circuit disposed on the oscillation circuit substrate to oscillate a signal having a predetermined oscillating frequency; and a dielectric resonator for setting the oscillating frequency, the dielectric resonator including:  
a dielectric substrate mounted on a surface of the oscillation circuit substrate;  
a TM010 mode resonator having a first electrode disposed on a first surface of the dielectric substrate and a second electrode disposed on a second surface of the dielectric substrate, at least one of the first and second electrodes being circular; and  
an excitation electrode disposed on the dielectric substrate, the excitation electrode being connected to the oscillation circuit and being coupled with the TM010 mode resonator,  
wherein the oscillation circuit includes a transmission line disposed on the surface of the oscillation circuit substrate and a ground electrode, and  
at least one of the first and second electrodes of the TM010 mode resonator is connected to a land disposed on the surface of the oscillation circuit substrate, and the land is connected to the ground electrode.
3. (Previously presented) The oscillator device according to claim 2, wherein the at least one of the first and second electrodes of the TM010 mode resonator is connected to the land with bumps.

4. (Currently amended) An [[The]] oscillator device according to claim 1, comprising:  
an oscillation circuit substrate;  
an oscillation circuit disposed on the oscillation circuit substrate to oscillate a signal  
having a predetermined oscillating frequency; and  
a dielectric resonator for setting the oscillating frequency, the dielectric resonator  
including:  
    a dielectric substrate mounted on a surface of the oscillation circuit substrate;  
    a TM010 mode resonator having a first electrode disposed on a first surface of  
    the dielectric substrate and a second electrode disposed on a second surface of the dielectric  
    substrate, at least one of the first and second electrodes being circular; and  
    an excitation electrode disposed on the dielectric substrate, the excitation  
    electrode being connected to the oscillation circuit and being coupled with the TM010 mode  
    resonator,  
    wherein the oscillation circuit includes a transmission line and a ground electrode on the  
    surface of the oscillation circuit substrate, and  
    at least one of the first and second electrodes of the TM010 mode resonator is connected  
    to the ground electrode disposed on the surface of the oscillation circuit substrate.

5. (Currently amended) The oscillator device according to claim [[1]] 2, further  
comprising:

    a frequency control circuit for controlling the oscillating frequency, the frequency  
    control circuit being disposed on the oscillation circuit substrate; and  
    a second excitation electrode disposed on the dielectric substrate, the second excitation  
    electrode coupled with the TM010 mode resonator and connected to the frequency control circuit.

6. (Currently amended) A transmission and reception device using the oscillator device  
set forth in claim [[1]] 2.

7. (Previously presented) The oscillator device according to claim 2, wherein the surface of the oscillation circuit substrate is a first surface, and the ground electrode is disposed on a second surface of the oscillation circuit substrate, the second surface opposing the first surface.

8. (Previously presented) The oscillator device according to claim 7, wherein the land is connected to the ground electrode via a through-hole passing through the oscillation circuit substrate.

9. (New) The oscillator device according to claim 4, further comprising:  
a frequency control circuit for controlling the oscillating frequency, the frequency control circuit being disposed on the oscillation circuit substrate; and

a second excitation electrode disposed on the dielectric substrate, the second excitation electrode coupled with the TM010 mode resonator and connected to the frequency control circuit.

10. (New) A transmission and reception device using the oscillator device set forth in claim 4.